












## Steam Hoses

# PREMIUM™ HEATER MASTER



								
mm	mm	mm	Bar	Bar	Bar	Kg/m	m	REF.
13	25	6	6	20	60	0.5	40	3213-11001
16	30	7	6	20	60	0.6	40	3213-11002
19	33	7	6	20	60	0.8	40	3213-11003
25	40	7.5	6	20	60	0.9	40	3213-11004
32	48	8	6	20	60	1.2	40	3213-11005
38	54	8	6	20	60	1.4	40	3213-11006
51	67	8	6	20	60	1.8	40	3213-11007

### RECOMMENDED FOR

Premium hot water (20 bar up to 90°C) delivery and steam hose up to 164°C, 6 bar working pressure in general industrial applications.

### TUBE

Black EPDM, smooth

### REINFORCEMENT

High tensile textile cord

### COVER

EPDM rubber, smooth, black. Extremely weather resistance cover

### TEMPERATURE

-20 °C to +164°C

### BURST PRESSURE

60 Bar

### ELECTRICALLY CONDUCTIVE

R < 10<sup>6</sup> Ohm

### STANDARDS

Exceeds BS 5122/A2

### BRANDING TRANSFER LABEL

PREMIUM™ HEATER MASTER - STEAM OPEN SYSTEM 6 BAR 164°C Ω

